


DATA

Voltage	12.00 V
Performance	9Ah C20 to 1.75V/cell at 25°C
Float Voltage	2.27V/cell at 20°C
Connection torque	na
Max Charge Current	1.80 A
Weight (Typical)	2.7 KG

LAYOUT



PERFORMANCES

[A] at 20°C

V / cell	min.	5	10	15	30	45	60	120	180	240	300	360	480	600
1,60		38,8	26,5	19,8	11,2	7,88	5,79	3,13	2,20		1,44			0,85
1,65		38,4	26,2	19,5	11,1	7,83	5,75	3,10	2,19		1,43			0,85
1,67		38,2	26,0	19,4	11,1	7,80	5,73	3,09	2,17		1,42			0,85
1,70		37,9	25,8	19,1	11,0	7,75	5,69	3,06	2,15		1,41			0,84
1,75		37,2	25,3	18,6	10,8	7,63	5,59	2,98	2,11		1,39			0,85
1,80		34,2	23,0	17,1	10,1	7,20	5,31	2,79	1,94		1,24			0,85
1,85														
1,90														

[W/cell] at 25°C

V / cell	min.	5	10	15	30	45	60	120	180	240	300	360	480	600
1,60		67,8	47,6	36,2	21,4	15,3	11,4	6,24	4,42		2,86			1,65
1,65		67,5	47,4	36,0	21,4	15,3	11,4	6,21	4,41		2,85			1,63
1,67		67,2	47,2	35,8	21,3	15,2	11,3	6,18	4,39		2,84			1,63
1,70		66,7	46,8	35,5	21,1	15,2	11,3	6,13	4,36		2,83			1,62
1,75		65,7	46,0	34,7	20,9	15,0	11,1	6,02	4,30		2,80			1,60
1,80		64,0	44,7	33,8	20,5	14,8	10,9	5,95	4,16		2,67			1,58
1,85		61,2	42,8	32,5	19,9	14,3	10,7	5,69	3,99		2,51			1,57
1,90														